

Edge Designs for 1-Layer Decorative Panels

The Heradesign decorative panels can be equipped with various edge designs in order to match the architectural concept and the planned method of installation.

As a result, Heradesign decorative panels can be used for almost all commercially available hanging systems and installation methods.

Abbreviation	Design	for	Heradesign® <i>superfine</i>			Heradesign® <i>fine</i>			Heradesign® <i>fine/A2</i> ***)		Heradesign® <i>micro</i>		Heradesign® <i>plano</i> ***)		Recommended profile width	References	Grid dimensions 2) 3)	Panel dimensions
			15	25	35	15	25	35	25	25	35	25	25	35				
Recommended standard edge designs and grid dimensions																		
GK		straight edge on all sides for screw mounting														1 3	600/600 1200/600	600/600 1200/600
AK-00		bevelled on long sides (5 mm bevel) for screw mounting														3	600/600, 625/625 1200/600, 1250/625	600/600, 625/625 1200/600, 1250/625
AK-01		bevelled on all sides (5 mm bevel) for screw mounting															600/600, 625/625 1200/600, 1250/625	600/600, 625/625 1200/600, 1250/625
SK-04*)		straight edges only for visible T-section undercut as of 35 mm thickness													24	1 2	600/600, 625/625 1200/600, 1250/625	594/594, 619/619 1194/594, 1244/619
SK-08		straight on the long side, front side with bevelled edges for Omega section (5 mm bevel)													20	2	620, 645	595/600, 620/625 595/1200, 620/1250
Special Designs																		
AK-02		shiplap on all sides for screw mounting														3	600/600, 1200/600 625/625, 1250/625	600/600, 1200/600 625/625, 1250/625
AK-03		shiplap on all sides with 5 mm bevel for screw mounting															600/600, 1200/600 625/625, 1250/625	600/600, 1200/600 625/625, 1250/625
SK-05		shiplap on all sides for visible T-section													24	2	600/600, 1200/600 625/625, 1250/625	594/594, 619/619 1194/594, 1244/619
SK-06		shiplap on all sides with 5 mm bevel for T-section													24	2	600/600, 1200/600 625/625, 1250/625	594/594, 619/619 1194/594, 1244/619
VK-09**)		concealed T-section for push-in mounting – panels grooved and bevelled on all sides (5 mm bevel)													35	3	600/600, 625/625 1200/600, 1250/625	600/600, 625/625 1200/600, 1250/625
VK-10**)		concealed T-section – panels can be disassembled – panels grooved and bevelled on all sides.													35	2 3	600/600 1200/600	615/600 615/1200
VK-12		shiplap all round on alternating sides with 5 mm bevel.														2 3	1190/590 1240/615	1200/600 1250/625
System Edges																		
SY-01		straight edges on all sides, grooved on the long sides, undercut on the cross sides for modo ceiling system															600/600 1200/600	596/600 1200/596
SY-02		grooved on the long sides, bevelled on all sides for Heradesign retaining claw														3	600/600, 625/625 1200/600, 1250/625	600/600, 625/625 1200/600, 1250/625
<p>1 The straight edge is not an exposed edge. Straight edge only produced at the express request of the customer.</p> <p>2 The billing dimensions or alternatively the ordering dimensions are always the grid dimensions.</p> <p>3 Installation pattern in cross joints requires very careful installation, because four visible panel edges have to meet at one point.</p>																		

Please note:

***) Heradesign® *plano* : Panel thickness only 25 mm, max. width 600 mm; for edge VK-09: bevel only 3 mm
 Heradesign® *fine/A2*: Panel thickness only 25 mm, max. width 600 mm

Attention:

*) Heradesign® *fine* and Heradesign® *superfine* are only available in the format 600/600 or alternatively 625/625 for a thickness of 15 mm and edge SK-04.
 **) Custom formats only on request – length ≤ 1800 mm (contact technical customer service)